



Rockingham **SCALEXTRIC Club**

FLY CLASSIC SPORTS & GT. RACING CHAMPIONSHIP

- **The following cars will be eligible to race:-**

Fly

Ferrari 512S, 512S Berlinetta, 512S Berlinetta CL, 250LM & 275LM
Porsche 906/Carrera 6
Porsche 908/2, 908/2 Flunder, 908/2 Flunder Langheck, 908/3
Porsche 917K, 917LH & 917/10 Turbo
Lola T70 Mk IIIb, Ford GT40 MkI & GT40 MkII

- Only sidewinder versions of the Fly cars are permitted.

GB Track

Chevron B19 & B21, Porsche 917PA (Spyder)

Scalextric

Ford GT40 MkI & GT40 MkII, Ferrari 330 P4/412P, Chaparral 2F

Spirit

Ferrari 512M

Sloter

Ferrari 312PB & 312PB long tail, Lola T280 & T290

Revell/Monogram

Lola T70 MkII

SRC

Porsche 907LH, 907K & 908, Alfa Romeo T33/TT12, Matra MS670

This list is based upon Classic Sports and GT cars of the 1960s and 1970s that are of generally similar construction and performance, which come with a sidewinder Mabuchi 'S' can (FC130) motor, a 19mm diameter spur gear and a fixed motor mount as standard.

If you think any car or should be added to or removed from this list please let us know.

Once a class has been selected for a mini series no alterations can be made to the rules for that class until after the conclusion of the mini series.

TECHNICAL REGULATIONS

1. Motors & Motor Mounts

- a. All eligible cars must be powered by a commercially available Mabuchi 'S' can (FC130) motor with a manufacturer's rating not exceeding 20,000rpm at 12volts.
 - If a motor is rated at a higher voltage a simple straight line graph will be used to determine the rpm at 12volts.
 - E.g. a motor rated at 23,000rpm @ 14volts.
 $23,000/14 = 1643 \times 12 = 19,716$ rpm @ 12volts.
 - Manufacturer's figures will be accepted as correct.
- b. Shortening the armature shaft is the only modification permitted to any motor.
- c. No modifications to the motor mount are permitted.
- d. Motor position in the chassis may not be altered in any way.
- e. Motors and/or motor mounts may be glued into place if desired.
- f. Rear-wheel drive only is permitted.

2. Gears

- a. All eligible cars must be fitted with a 6.5mm minimum diameter 11 tooth pinion and a 19mm diameter 36 tooth spur gear.
- b. The original gears supplied by the car manufacturer may be used provided that they comply with rule 2a or the following Slot.It gears may be substituted if desired.
 - Pinion SIPS11 6.5mm diameter x 11 tooth
 SIPI67110 6.75mm diameter x 11 tooth
 - Spur gear SIGS02 19mm diameter x 36 tooth
 SIGS1936 19mm diameter x 36 tooth
 - Other brands of after market gears will be permitted provided they are identical in diameter and tooth numbers to the Slot.It gears listed above.
- c. Pinions may be glued to motor shafts and spur gears may be glued to axles.

3. Wheels

- a. Any wheels fitted as original equipment by the manufacturer to any eligible car may be used, and may be fitted to any other eligible car, provided they are of the correct size, both front and rear, for the car they are fitted to.
- b. Any other brand of plastic or machined aluminium wheels may be substituted if desired provided they are of the correct size, both front and rear, for the car they are fitted to.
- c. All wheels must be of a style that represents a real wheel as used on the real car or have suitable inserts fitted.
- d. Wheels may be glued to axles if desired.

4. Tyres

- a. Any brand of solid rubber tyre may be used subject to the following restrictions;
 - Front tyres: Minimum diameter 16mm, minimum width 8mm.
 - Rear tyres: Minimum diameter 20mm, maximum width 12mm.
- b. Tyre treads must not protrude outside the car bodywork when viewed from above.
- c. Front axles must have any side-to-side movement restricted to comply with Rule 4b.
- d. Tyres may be glued onto the wheels, and may be sanded true.
- e. Front tyres may be coated with nail varnish, super glue or similar.
- f. Any tyre dressing/cleaner used must not leave a residue on the tyres or track.
- g. Sponge tyres and tyre dressings (goop) of any kind are not permitted.
- h. Tyres made from, or containing, Silicone must not be used.**

5. Rear Axles

- a. Rear axles are free choice but must not extend beyond the outer face of any wheel.
See also Rule 4b.
- b. Any type of plain rear axle bearings may be fitted, and may be glued into place.

6. Front Axles

- a. Front axles are free choice but must not extend beyond the outer face of any wheel.
See also Rules 4b and 4c.
- b. Any type of plain front axle bearings may be fitted and may be glued into place.
- c. Cars fitted with stub axles may have them replaced with a single, solid axle if desired.

7. Slot Guide

- a. All cars must have one slot guide only.
- b. All cars must be fitted with a standard depth slot guide.*
- c. Any car may have an easy-fit guide replaced with a conventional wired guide with the minimum necessary modification made to the chassis.
- d. Guide to motor wires and pick up braids are free choice.

8. Lights etc.

- a. Any car fitted with working lights may have the light bulbs, LED's, wiring, PC board, and any other internal fittings removed, but must retain all external lenses.

9. Ballast

- a. Ballast weight may be added to any car as desired, provided that it is placed within the confines of the body and chassis and is firmly glued in place.
- b. Traction magnets may be retained or removed as desired.

10. Body and Chassis

- a. Bodies and chassis must be used complete and unmodified except as detailed below.
- b. Bodies may be repainted provided that doing so does not distort the body.
- c. White body kits must be fully painted.
- d. All cars must have a realistic colour scheme and carry at least three racing numbers.
- e. The original interior must be retained complete, include a full length driver and may be glued in place.
- f. Vacuum formed or other light weight interiors are not permitted.
- g. No part of the chassis or running gear may be visible through the cockpit/cabin area.
- h. Windscreen and window mouldings must be retained, and be complete and original.
- i. Wheel arches may not be enlarged in any way but moulding flash may be cleaned off.
- j. Rear view mirrors and spare wheels and tyres may be omitted if desired but all other detail parts must remain fitted.
- k. Cars that have wings must have them securely fitted at the start of racing.
- l. The chassis must be the chassis originally intended for the body being used.
- m. Chassis ride height may not be lowered in any way.
- n. Body to chassis mountings may not be lowered in any way.
- o. Minor scraping or sanding of the body sides and/or chassis edges is permitted to allow the body to move freely on the chassis.
 - This includes removal of any internal pegs etc. that rest on the motor, axle bearings or chassis sides.
 - Removal of other parts of the body or chassis for this purpose is not permitted.
- p. Body fixing screws are free choice and may be left loose.
- q. Adhesive tape or 'blue tack' must be placed over the body fixing screw holes to prevent screws from falling out.

11. Ground Clearance

- a. There is no minimum ground clearance rule but at no time may the body, chassis, motor or gears touch the track surface in normal use.
- b. When the car, race ready, is placed on a slotted, flat surface, all 4 tyres must touch the surface and all 4 wheels must rotate when it is pushed forward.**

12. Finally...

If the rules do not expressly say that you can do something then you cannot do it.

***Definition of a 'standard depth slot guide'**

- a. Any slot guide supplied as original equipment by the manufacturer with any ready-to-run slot car eligible for the class.
- b. Any aftermarket slot guide intended for use in any ready-to-run slot car which can be fitted without modification to the guide or guide mount and having a blade depth, excluding braids, of no more than 7mm.

Index to amendments

<u>Issue No</u>	<u>Date</u>	<u>Amendment</u>
1	22/05/00	First draft.
1A	26/05/00	Allow the removal of mirrors.
1B	10/11/00	Add Porsche 908 Flunder Langheck & Porsche 908/3.
1C	24/03/01	Add GB Track Porsche 917 Spyder & Chevron B19/21.
1D	15/04/02	Add Fly Ferrari 512S Berlinetta CL.
1E	06/09/02	Add Fly Porsche 917/10 Turbo.
1F	06/11/02	Amend to allow Scalextric GT40.
1G	26/11/03	Add Fly GT40
1H	16/01/04	Exclude Scalextric GT40
1I	28/04/05	Allow NSR Tyres
1J	15/06/06	Add Porsche 906 and 917LH
1K	06/03/09	Add Ferrari 250 and 275 LM
2	23/05/09	Allow Scaleauto SC-0008 20,000rpm Silver can motor.
2b	24/12/10	Add Scaleauto SC-0020 20,000rpm Blue can motor.
2c	05/11/12	Add Scaleauto SC-0008B 20,000rpm Silver can motor. Allow Slot.It Gears and aluminium wheels.
2d	21/12/12	Allow any 'standard depth' slot guide to be used. Add 'definition of a standard depth slot guide'.
3	18/06/13	Revised to include cars from Scalextric, Spirit, Sloter & Revell/Monogram. Also to allow any 20k Mabuchi S motor.
4	01/08/13	Simplify and clarify using standard wording for each section.
4b	19/12/14	Amend gear rule to 'all cars must have 11:36 gears'. Add SRC Porsche 907, 908, Alfa T33/TT12 and Matra MS670.